MATERIALS CREDITS DOCUMENTION SHEET

LEED[™] - GREEN BUILDING RATING SYSTEM

MATERIALS OR PRODUCT:		TOUCH 'N SEAL 1.0 PCF FR Low Density Open Cell Foam		
	(LESS LABOR AND			
EQUIPMENT):				
Contractor/Installer:		Manufacturer:	Convenience Products	
Address:		Manufacturer Address:	866 Horan Drive	
			Fenton	MO 63026
Manufacturer Contact: Michael Sites, Technical Services Manager, (800) 325-6				325-6180
Signed by:	Michael Sites	Da	te	5/11/16
Company:	Convenience Products			

Instructions to Contractor/Installer: Please complete the following information in all appropriate categories. Use one documentation sheet for each product or material (e.g. tile and grout each get their own sheet). Attach any other additional information to this sheet (e.g. cut sheets, letters from manufacturers, etc.)

LEED v4 for Building Design and Construction: Homes

Step A – Energy and Atmosphere

Performance Path – Annual Energy Use (1-29 points possible) Prescriptive Path – Air Infiltration (1-2 points possible) Prescriptive Path – Envelope Insulation (1-2 points possible)

1.0 PCF Low	Functions as an air barrier and thermal insulation, this polyurethane
Density	foam product helps building to achieve higher levels of energy efficiency.

Step B – Materials & Resources

Construction Waste Management (0.5-3 points possible)

1.0 PCF Low	This foam sealant expands and seals without requiring trimming;
Density	results in no waste. Steel can is able to be recycled.

Step C – Indoor Environmental Quality

Low-Emitting Products (1-3 points possible)

1.0 PCF Low	0 g/l; below CA Section 01350 limits of 250 g/L VOC for
Density	Architectural Sealants.

LEED SUBMITTALS