Printing date: 08/26/2016

Revision: 08/26/2016

Convenience

products

1 Identification

· Product identifier

- · Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A
- Product code: EHS 2921

· Recommended use and restriction on use

- · Recommended use: Polyurethane-sealant
- Restrictions on use: See Sections 8 and 10 for further information.

· Details of the supplier of the Safety Data Sheet

• Manufacturer/Supplier: Convenience Products, division of Clayton Corp. 866 Horan Drive Fenton, MO 63026-2416

Phone: 636-349-5855

• Emergency telephone number: ChemTel Inc. (800)255-3924, +1 (813)248-0585

2 Hazard(s) identification

· Classification of the substance or mixture

Press. Gas H280 Contains gas under pressure; may explode if heated.

- Acute Tox. 4 H332 Harmful if inhaled.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2A H319 Causes serious eye irritation.
- Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· Label elements

· GHS label elements

- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms:



· Signal word: Danger

Hazard statements:

H280 Contains gas under pressure; may explode if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

(Cont'd. on page 2)

Printing date: 08/26/2016

Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

	(Cont'd. of page 1)
H373 May caus	se damage to organs through prolonged or repeated exposure.
 Precautionary 	statements:
P260	Do not breathe mist/vapors/spray.
P284	[In case of inadequate ventilation] wear respiratory protection.
P264	Wash thoroughly after handling.
P280	Wear protective gloves and eye protection.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P305+P351+P3	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Other hazard	S There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	40-60
	 Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 	
101-68-8	4,4'-methylenediphenyl diisocyanate	20-40
	 Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 	
811-97-2	Norflurane	10-209
	Press. Gas, H280 Simple Asphyxiant	
156-60-5	halogenated hydrocarbon	1-2.5%
	 Flam. Liq. 2, H225 Acute Tox. 4, H332 	

For the wording of the listed Hazard Statements refer to section 16.

(Cont'd. on page 3)

Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

(Cont'd. of page 2)

First-aid measures	
Description of first aid measures	
General information:	
Take affected persons out into the fresh air.	
Do not leave affected persons unattended.	
Immediately remove any clothing soiled by the product.	
Symptoms of poisoning may even occur after several hours; therefore medical obser	rvation for at least 4
hours after the accident.	
After inhalation:	
Supply fresh air and to be sure to call for a doctor.	
In case of unconsciousness place patient stably in side position for transportation.	
After skin contact:	
Do not pull solidified product away from the skin.	
Immediately wash with water and soap and rinse thoroughly.	
If skin irritation or rash occurs: Get medical advice/attention.	
After eye contact:	
Protect unharmed eye.	
Do not remove contact lenses if worn.	
Rinse opened eye for several minutes under running water. If symptoms persist, cons	sult a doctor.
Seek immediate medical advice.	
After swallowing:	
Unlikely route of exposure.	
Rinse out mouth and then drink plenty of water.	
Do not induce vomiting; immediately call for medical help.	
Most important symptoms and effects, both acute and delayed:	
Asthma attacks	
Headache	
Coughing	
Breathing difficulty	
Dizziness	
Cyanosis	
Allergic reactions	
Irritant to skin and mucous membranes.	
Irritant to eyes.	
Danger:	
Danger of impaired breathing.	
Danger of pulmonary edema.	
Danger of convulsion.	
May cause damage to organs through prolonged or repeated exposure.	
Condition may deteriorate with alcohol consumption.	
Indication of any immediate medical attention and special treatment needed: If swallowed, gastric irrigation with added, activated carbon.	
If swallowed or in case of vomiting, danger of entering the lungs.	
Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.	
Medical supervision for at least 48 hours.	
If necessary oxygen respiration treatment. Later observation for pneumonia and pulmonary edema.	
Later observation for pheumonia and pulmonary edema.	(Cont'd. on page
	(Soma, on page

(Cont'd. on page 4)

Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

(Cont'd. of page 3)

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: None.
- Special hazards arising from the substance or mixture Danger of receptacles bursting because of high vapor pressure if heated.
 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases. Wear fully protective suit.

• Additional information:

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol. Remove persons from danger area. Ensure adequate ventilation.
 Wear protective equipment. Keep unprotected persons away.
 Protect from heat.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

 \cdot Methods and material for containment and cleaning up:

Allow to solidify. Pick up mechanically. Clean the affected area carefully; suitable cleaners are: Organic solvent

 Reference to other sections: See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

· Handling

· Precautions for safe handling:

Use only in well ventilated areas.

Keep away from heat and direct sunlight.

· Information about protection against explosions and fires:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.

(Cont'd. on page 5)

Printing date: 08/26/2016 Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

(Cont'd. of page 4)

Do not spray on a naked flame or any incandescent material. Keep respiratory protective device available.

• Conditions for safe storage, including any incompatibilities • Storage

Requirements to be met by storerooms and receptacles: Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
Information about storage in one common storage facility: Store away from foodstuffs.
Do not store together with acids.
Store away from oxidizing agents.
Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
Store in a cool place. Heat will increase pressure and may lead to the receptacle b

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from heat and direct sunlight.

• Specific end use(s): No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components w	ith limit values that require monitoring at the workplace:
-	ethylenediphenyl diisocyanate
PEL (USA)	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
REL (USA)	Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min
TLV (USA)	Long-term value: 0.051 mg/m ³ , 0.005 ppm
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin; S
EV (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm
LMPE (Mexico)	Long-term value: 0.005 ppm
811-97-2 Norflu	rane
WEEL (USA)	Long-term value: 1000 ppm
156-60-5 halog	enated hydrocarbon
PEL (USA)	Long-term value: 790 mg/m ³ , 200 ppm
REL (USA)	Long-term value: 790 mg/m ³ , 200 ppm
TLV (USA)	Long-term value: 793 mg/m ³ , 200 ppm
EL (Canada)	Long-term value: 200 ppm
EV (Canada)	Short-term value: 990 mg/m³, 250 ppm Long-term value: 790 mg/m³, 200 ppm
LMPE (Mexico)	Long-term value: 200 ppm
L	(Cont'd. on page 6)

Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

(Cont'd. of page 5)

- Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:
- The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- Engineering controls: No relevant information available.
- · Breathing equipment:



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

Use suitable respiratory protective device when high concentrations are present.

Suitable respiratory protective device recommended.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Gloves should provide protection from freezing temperatures.

· Eye protection:

Contact lenses should not be worn.



Safety glasses

Body protection: Protective work clothing

- Limitation and supervision of exposure into the environment No relevant information available.
- Risk management measures See Section 7 for additional information.

 Information on basic physical and chemical properties Appearance: 		
Form:	Aerosolized liquid with compressed gas in cylinders	
Color:	Cream colored	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Melting point/Melting range:	Not applicable, as aerosol.	
· Boiling point/Boiling range:	Not applicable, as aerosol.	

Printing date: 08/26/2016

Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

		(Cont'd. of page
Flash point:	Not applicable, as aerosol.	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Danger of explosion:	Not determined.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Not determined.	
Vapor pressure at 20 °C (68 °F):	5716 hPa (4287 mm Hg)	
Density at 20 °C (68 °F):	1.03 g/cm³ (8.595 lbs/gal)	
Relative density:	Not determined.	
Vapor density:	Not determined.	
Evaporation rate:	Not applicable.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
VOC (California):	32.8 g/L (EPA Method 24)	
Other information	No relevant information available.	

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:
- Danger of receptacles bursting because of high vapor pressure if heated.
- Possibility of hazardous reactions: Reacts with alcohols, amines, aqueous acids and alkalis. Contact with acids releases toxic gases. Reacts with oxidizing agents. Exothermic polymerization.
 Conditions to avoid: Store away from oxidizing agents.
- Conditions to avoid. Store away from oxidizing agents.
- \cdot Incompatible materials: Contact with acids liberates toxic gas.
- Hazardous decomposition products: Carbon monoxide and carbon dioxide
- Ammonia Isocyanate

(Cont'd. on page 8)

Printing date: 08/26/2016

Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

(Cont'd. of page 7)

3

3

Nitrogen oxides

11 Toxicological information

 Information on toxicologic 	al effects
Aquita taviaituu	

- Acute toxicity:
- \cdot LD/LC50 values that are relevant for classification:
- 101-68-8 4,4'-methylenediphenyl diisocyanate
- Oral LD50 2200 mg/kg (mouse)
- · Primary irritant effect:
- On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- Sensitization: May cause sensitisation by inhalation and skin contact.

· IARC (International Agency for Research on Cancer):

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

• NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

• **Probable route(s) of exposure:** Inhalation.

Eye contact.

- Skin contact.
- \cdot Acute effects (acute toxicity, irritation and corrosivity):
- Harmful if inhaled.

Irritating to eyes, respiratory system and skin.

- · Repeated dose toxicity: Possible risk of irreversible effects.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: May cause respiratory irritation.
- STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity The product contains materials that are harmful to the environment.
- · Persistence and degradability The product is partially biodegradable. Significant residuals remain.
- Bioaccumulative potential: Does not accumulate in organisms
- Mobility in soil: No relevant information available.

(Cont'd. on page 9)

Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

(Cont'd. of page 8)

· Additional ecological information

· General notes:

At present there are no ecotoxicological assessments.

This statement was deduced from products with a similar structure or composition.

Due to the consistence and the low watersolubility of the product a bioavailability is not probable.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

· Other adverse effects: No relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

· Uncleaned packagings

· Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, ADR, IMDG, IATA	UN3500
· UN proper shipping name	
· DOT, IATA	Chemical under pressure, n.o.s. (Fluorinate Hydrocarbon, Nitrogen)
ADR	3500 CHEMICAL UNDER PRESSURE, N.O.3 (Fluorinated Hydrocarbon, Nitrogen)
IMDG	CHEMICAL UNDER PRESSURE, N.O.S. (Fluorinate Hydrocarbon, Nitrogen)
Transport hazard class(es)	
DOT	
· Class	2.2

Printing date: 08/26/2016

Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

	(Cont'd. of pa
Label	2.2
ADR	
	
Class	2 8A Gases
Label	2.2
IMDG, IATA	
<u>-</u>	
Class	2.2
Label	2.2
Packing group	This UN-number is not assigned a packing group.
Environmental hazards	
Marine pollutant:	No
Special precautions for user	Warning: Gases
Danger code (Kemler):	20
EMS Number:	F-D,S-U
Transport in bulk according to Annex	ll of
MARPOL73/78 and the IBC Code	Not applicable.
Regulatory information	
Sofoty boolth and anyironmartel to	gulations/legislation specific for the substance

· United States (USA)

·SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

(Cont'd. on page 11)

Printing date: 08/26/2016

Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

-		(Cont'd. of page
	n 65 (California)	
	known to cause cancer:	
None of the	e ingredients are listed.	
Chemicals	s known to cause reproductive toxicity for females:	
None of the	e ingredients are listed.	
Chemicals	s known to cause reproductive toxicity for males:	
None of the	e ingredients are listed.	
Chemicals	s known to cause developmental toxicity:	
None of the	e ingredients are listed.	
Carcinoge	nic categories	
EPA (Envi	ronmental Protection Agency):	
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	CE
101-68-8	4,4'-methylenediphenyl diisocyanate	CE
IARC (Inte	rnational Agency for Research on Cancer):	
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	
101-68-8	4,4'-methylenediphenyl diisocyanate	
NIOSH-Ca	(National Institute for Occupational Safety and Health):	
None of the	e ingredients are listed.	
Canadian	Domestic Substances List (DSL):	
All ingredie	nts are listed.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 07/07/2016 / -

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health LDLo: Lowest Lethal Dose Observed Press. Gas: Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

(Cont'd. on page 12)

Printing date: 08/26/2016

Revision: 08/26/2016

Trade name: Touch 'n Seal FR Standard Foam Kit 110 Side A

(Cont'd. of page 11)

Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 • **Sources**

SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com