

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

1. Identification

This Safety Data Sheet is available in American Spanish upon request. Los Datos de Serguridad pueden obtenerse en Espanol si lo riquiere.

Product Name:	Touch N Seal Quick Cure Cylinder High Yield PU Foam Sealant	Revision Date:	11/29/2018
Product UPC Number:	075650000625, 075650000649	Supercedes Date:	10/11/2018
Product Use/Class:	Foam Sealant/Adhesive	SDS No:	00047365508
Manufacturer:	DAP Foam, Inc. 307 Integram Drive Pacific, MO 63069 888-327-8477 (non - emergency matters) SDS Coordinator: MSDS@dap.com Emergency Telephone: Transportation: 1-800-535-5053 1-352-323-3500 Poison Control: 1-800-222-1222	Preparer:	Regulatory and Environmental Affairs

2. Hazards Identification

GHS Classification

Acute Tox. 4 Inhalation, Carc. 2, Comp. Gas, Eye Irrit. 2, Resp. Sens. 1, Skin Irrit. 2, Skin Sens. 1, STOT RE 2, STOT SE 3 NE, STOT SE 3 RTI

Symbol(s) of Product



Signal Word Danger

Possible Hazards 23% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS		
Compressed Gas	H280	Contains gas under pressure; may explode if heated.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Respiratory Sensitizer, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
GHS LABEL PRECAUTIONARY STATE	MENTS	
P201		ial instructions before use.
P260	Do not breat	the dust/fume/gas/mist/vapours/spray.
P264	Wash thorou	ughly after handling.
P271	Use only out	tdoors or in a well-ventilated area.
P272	Contaminate	ed work clothing should not be allowed out of the workplace.
P280	Wear protect	tive gloves/protective clothing/eye protection/face protection.
P281	Use persona	al protective equipment as required.
P284	[In case of ir	nadequate ventilation] wear respiratory protection.
P302+P352		: Wash with plenty of soap and water.
P304+P340	IF INHALED	: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338		Rinse cautiously with water for several minutes. Remove contact lenses, if
		easy to do. Continue rinsing.
P308+P313		or concerned: Get medical advice/attention.
P312		ON CENTER or doctor/physician if you feel unwell.
P321	•	tment (see on this label).
P332+P313		on occurs: Get medical advice/attention.
P333+P313		on or rash occurs: Get medical advice/attention.
P337+P313	•	on persists: Get medical advice/attention.
P342+P311	•	ng respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362		taminated clothing.
P403+P233		ell-ventilated place. Keep container tightly closed.
P405	Store locked	•
P410+P403		sunlight. Store in a well-ventilated place.
P501	Dispose of c	contents/container to
GHS SDS PRECAUTIONARY STATEME	ENTS	
P363	Wash conta	minated clothing before reuse.

P363 Wash contaminated clothing before reuse.

3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. % GHS Symbols	GHS Statements
Polymeric diphenylmethane diisocyanate	9016-87-9	15-40 GHS07	H332
1,1,1,2-Tetrafluoroethane (HFC-134A)	811-97-2	10-30 GHS07	H336

SAP Number: 9700050106

Revision Date: 11/29/2018

4,4'-Methylene diphenyl diisocyanate (MDI)	101-68-8	10-30 GHS07-GHS08	H315-317-319-332-334-335-351 -373
Propan-2-oxide, 1,3-dichloro-, phosphate	13674-87-8	7-13 GHS08	-373 H351
POLYPROPYLENE GLYCOLS	25322-69-4	5-10 No Information	No Information
Tris(2-chloro-1-methylethyl) phosphate	13674-84-5	3-7 GHS07	H302-332
1,2-trans-Dichloroethylene	156-60-5	1-5 GHS02-GHS07	H225-302-332

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: No Information

FIRST AID - SKIN CONTACT: Use a rag to remove excess foam from skin and remove contaminated clothing. Use of a solvent, such as acetone (nail polish remover) or mineral spirits, may help in removing uncured foam residue from clothing or other surfaces (avoid eye contact). Cured foam may be physically removed by persistent washing with soap and water. If irritation develops, use mild skin cream. If irritation persists, obtain medical attention.

FIRST AID - EYE CONTACT: No Information

FIRST AID - INGESTION: No Information

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may burst if exposed to extreme heat or fire.

SPECIAL FIREFIGHTING PROCEDURES: No Information

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Uncured product is very sticky, so carefully remove the bulk of the foam by scraping it up and then immediately remove residue with a rag and solvent such as polyurethane cleaner, mineral spirits, acetone (nail polish remover), paint thinner, etc. Once the product has cured, it can only be removed physically by scraping, buffing, etc. Dispose as plastic waste (foam plastic) in accordance with all applicable guidelines and regulations.

7. Handling and Storage

HANDLING: Make sure nozzle is directed away from yourself prior to discharge. Keep away from open flames, hot surfaces and sources of ignition. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Do not breathe dust. While dry sanding, use of a NIOSH-approved dust mask is recommended. Contains isocyanates. See information supplied by the manufacturer. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

STORAGE: Protect material from direct sunlight. Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store at temperatures above 120 degrees F. Store containers away from excessive heat and freezing.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits <u>Chemical Name ACGIH TLV-TWA ACGIH-TLV STEL OSHA PEL-TWA OSHA PEL</u>				
Polymeric diphenylmethane diisocyanate		N.E.	N.E.	N.E.
1,1,1,2-Tetrafluoroethane (HFC-134A) 4,4'-Methylene diphenyl diisocyanate	N.E. 0.005 ppm TWA	N.E. N.E.	N.E. N.E.	N.E. 0.02 ppm Ceiling, 0.2
(MDI)	Methylene bisphenyl isocyanate (MDI)			mg/m3 Ceiling
Propan-2-oxide, 1,3-dichloro-, phosphate	N.E.	N.E.	N.E.	N.E.
POLYPROPYLENE GLYCOLS	N.E.	N.E.	N.E.	N.E.
Tris(2-chloro-1-methylethyl) phosphate	N.E.	N.E.	N.E.	N.E.
1,2-trans-Dichloroethylene	200 ppm TWA	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



SKIN PROTECTION: Wear protective gloves.



EYE PROTECTION: No Information



OTHER PROTECTIVE EQUIPMENT: No Information



HYGIENIC PRACTICES: Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

Appearance: Odor:		
Density, g/cm3:		
Freeze Point, °C:		
Solubility in Water: Decomposition Temperature,	°C:	
Boiling Range, °C:	0.	
Minimum Flash Point, °C:		
Evaporation Rate: Vapor Density:		
Combustibility:		[

Cream Slight Solvent 0.36 - 0.40 Not Established No Information Not Established N.E. - N.E. Not Applicable Faster Than n-Butyl Acetate Heavier Than Air Does not support combustion Physical State: Odor Threshold: pH: Viscosity (mPa.s): Partition Coeff., n-octanol/water: Explosive Limits, %: Auto-Ignition Temperature, °C Vapor Pressure, mmHg: Flash Method: Flammability, NFPA: Foam Not Established Not Applicable Not Applicable Not Established Not Established Not Established Not Applicable Non-Flammable

(See "Other information" Section for abbreviation legend) (If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: No Information

CONDITIONS TO AVOID: Do not breathe dust. Avoid dust formation in confined areas. Excessive heat and freezing.

INCOMPATIBILITY: No Information

HAZARDOUS DECOMPOSITION PRODUCTS: No Information

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Prolonged, repeated, or high exposures may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation. Mist and vapors may cause eye irritation. Foam

contact can cause physical damage due to adhesive character.

EFFECT OF OVEREXPOSURE - INGESTION: No Information

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Prolonged or repeated inhalation of dust may cause lung damage.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Inhalation, Eye Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

Chemical Name Polymeric diphenylmethane diisocyanate	<u>Oral LD50</u> 49000 mg/kg Rat	<mark>Dermal LD50</mark> ≥9400 mg/kg Rabbit	Vapor LC50 N.I.
1,1,1,2-Tetrafluoroethane (HFC-134A)	N.I.	N.I.	N.I.
4,4'-Methylene diphenyl diisocyanate (MDI)	31600 mg/kg Rat	9400 mg/kg Rabbit	N.I.
Propan-2-oxide, 1,3-dichloro-, phosphate	3160 mg/kg Rat	>4640 mg/kg Rabbit	N.I.
POLYPROPYLENE GLYCOLS	3750 mg/kg Rat	N.I.	N.I.
Tris(2-chloro-1-methylethyl) phosphate	1500 mg/kg Rat	>5000 mg/kg Rabbit	N.I.
1,2-trans-Dichloroethylene	1235 mg/kg Rat	5000 mg/kg Rabbit	N.I.
	Polymeric diphenylmethane diisocyanate 1,1,1,2-Tetrafluoroethane (HFC-134A) 4,4'-Methylene diphenyl diisocyanate (MDI) Propan-2-oxide, 1,3-dichloro-, phosphate POLYPROPYLENE GLYCOLS Tris(2-chloro-1-methylethyl) phosphate	Polymeric diphenylmethane diisocyanate49000 mg/kg Rat1,1,1,2-Tetrafluoroethane (HFC-134A)N.I.4,4'-Methylene diphenyl diisocyanate (MDI)31600 mg/kg RatPropan-2-oxide, 1,3-dichloro-, phosphate3160 mg/kg RatPOLYPROPYLENE GLYCOLS3750 mg/kg RatTris(2-chloro-1-methylethyl) phosphate1500 mg/kg Rat	Polymeric diphenylmethane diisocyanate49000 mg/kg Rat>9400 mg/kg Rabbit1,1,1,2-Tetrafluoroethane (HFC-134A)N.I.N.I.4,4'-Methylene diphenyl diisocyanate (MDI)31600 mg/kg Rat9400 mg/kg RabbitPropan-2-oxide, 1,3-dichloro-, phosphate3160 mg/kg Rat>4640 mg/kg RabbitPOLYPROPYLENE GLYCOLS3750 mg/kg RatN.I.Tris(2-chloro-1-methylethyl) phosphate1500 mg/kg Rat>5000 mg/kg Rabbit

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: No Information

13. Disposal Information

DISPOSAL INFORMATION: Contents under pressure. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Before disposing of containers, relieve container of any remaining product and pressure. Empty cylinders, once relieved of all pressure, can be disposed of as non-hazardous waste.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT UN/NA Number:	UN3500
DOT Proper Shipping Name:	Chemical under pressure, n.o.s.
DOT Technical Name:	(Fluorinated hydrocarbon, Nitrogen)
DOT Hazard Class:	2.2 Non-flamm compressed gas
Hazard SubClass:	N.A.
Packing Group:	N.A.

15. Regulatory Information

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	CAS-No.
Polymeric diphenylmethane diisocyanate	9016-87-9
4,4'-Methylene diphenyl diisocyanate (MDI)	101-68-8

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt. This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

16. Other Informati	ion			
Revision Date:		11/29/2018	Supersedes Date: 10/11/2018	
Reason for revision:		Product Composition Changed Substance and/or Product Properties Changed in Section(s): 01 - Product Information 05 - Flammability Information 11 - Toxicological Information 16 - Other Information		
Datasheet produced by: HMIS Ratings:		Regulatory Departm	ent	
Health:	Flammability:	Reactivity:	Personal Protection:	
2*	1	2	×	

VOC Less Water Less Exempt Solvent, g/L: 42.1

VOC Material, g/L: 14

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 3.9

VOC Actual, Wt/Wt%: 3.9

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.