



## Firestopping Caulk

### 1. PRODUCT NAME

Touch 'n Seal® Firestopping Caulk

### 2. DISTRIBUTOR

Convenience Products

866 Horan Drive

Fenton, MO 63026-2416 USA

Phone: (636) 349-5333

(800) 325-6180

Fax: (636) 349-5335

### 3. PRODUCT DESCRIPTION

- Red Color for Ease of Inspection
- Rated 2000°F for 4 Hours
- Non-Toxic
- Non-Corrosive
- Environmentally Safe
- Unaffected by Freeze-Thaw

**Basic Use:** Touch 'n Seal® Firestopping Caulk is a non-combustible sealant used for firestopping applications around plumbing, duct work, wiring, framing around chimneys, masonry, other penetrations and construction voids. Product is used in construction where an ASTM-E136 non-combustible sealant is required.

Firestopping Caulk is colored red for ease of inspection, is non-corrosive, non-toxic, environmentally safe, and paintable when dry. Product withstands 2000°F for four hours.

### 4. TECHNICAL DATA

- ASTM-E136
- Non-Combustible
- 61RF
- Shelf Life: 12 months

### 5. INSTALLATION

Read all instructions and safety information (MSDS) prior to use of any product.

**Surface Preparation:** Surface should be clean and free of oil and loose debris. Openings larger than one inch should be pre-filled with a noncombustible supporting filler such as mineral wool to maximize yield.

**Application:** Touch 'n Seal Firestopping Caulk is easily applied with a caulk gun, trowel or other suitable tool. The non-sagging quality of this product provides a cost efficient means of sealing through penetrations with no waste.

**Storage:** Store below 160°F. Unopened containers are not affected by freeze-thaw cycles. If frozen, thaw prior to use.

**Limitations:** Do not apply at temperatures below 32°F, in continuously wet areas or in expansion joints. Building codes will vary according to geography and the intended use of the structure. Approved use of any product is the discretion and sole authority of the local code enforcement agency.

### 6. PRODUCT SAFETY

Touch 'n Seal® Firestopping Caulk meets or exceeds the ASTM-E136 test standards.