



Touch 'n Seal® Storm Bond™ Roof Tile Adhesive

Touch 'n Seal Storm Bond Roof Tile Adhesive has received the following approvals and listings:

- Florida Building Code listing FL 14506-R2
- Miami-Dade County Product Control Approved

**MIAMI-DADE COUNTY
APPROVED**

- Member: Tile Roofing Institute



AVAILABLE UNIT SIZES

- Storm Bond Roof Tile Adhesive – 24 oz (680 g)
Item Number 4004529470
- Storm Bond Roof Tile Adhesive – 23 lb (10.4 kg)
Complete – Item Number 4004517170
Replacement – Item Number 4004517180

FEATURES/BENEFITS

- Strong uplift results
- Best for high winds
- Highest compressive strength
- Walk on in 2 hours
- Approved for use with both clay and concrete tiles
- Ideal for installing cut tiles at hip and valleys
- Saves labor and material costs in new, re-roof and repair installations
- Easy to use
- No ozone depleting chemicals

TESTED PROPERTIES

- ASTM E84 Surface Burning Characteristic
Flame Spread – 5
Smoke Development – 30
- ASTM E96 Water Vapor Transmission – 2.39 perm-in.
- ASTM D1621 Compressive Strength
Parallel To Rise – 49.2 lbs/in² (3.46 kg/cm²)
Perpendicular To Rise – 41.68 lbs/in² (2.93 kg/cm²)
- ASTM D1622 Density – 1.8 lbs/ft³ (30.1 kg/m³)
- ASTM D1623 Tensile Strength, Parallel To Rise – 72.18 lbs/in² (5.07kg/cm²)
- ASTM D2126 Thermal and Humid Aging – Dimensional Stability
-40°F(-40°C), 14 days – 0.1%
158°F (70°C), 100% Relative Humidity, 14 days – 6.0%
- ASTM D2842 Water Absorption – 8.2%
- ASTM D2856 Open Cell Content – 13.1%
- TAS 101-95 Static Uplift Resistance – Pass

Touch 'n Seal Storm Bond Roof Tile Adhesive is available throughout the world. Contact Convenience Products Customer Service at 800-325-6180 or FAX 636-349-5335 for distributor information. Visit our website at touch-n-seal.com.