



# TECH DATA SHEET

## 1. PRODUCT NAME

Touch 'n Seal® No-Warp® Window & Door Insulating Sealant

## 2. MANUFACTURER

DAP Foam Inc.  
307 Integram, Pacific, MO 63069 USA

(800) 329-6886

FAX (636) 349-5335

E-mail support@touch-n-seal.com

Website: www.touch-n-seal.com

## 3. PRODUCT DESCRIPTION

Touch 'n Seal No-Warp is formulated to permanently seal around doors, windows and skylights without bowing jambs or deflecting frames. No-Warp exerts up to 95% less bowing pressure than competitive foams that may inhibit or prevent proper opening and closing of fenestrations.

No-Warp conforms to AAMA 812-04 for low-pressure foams. No-Warp air seals, insulates, blocks drafts, moisture and insects providing improved comfort and reduced energy usage. No-Warp one-component expanding polyurethane foam sealant is formulated to meet the insulating and air sealing requirements of the professional commercial, industrial, agricultural and residential contractor.

Moisture curing No-Warp foam sealant is applied with a foam applicator gun, once cured, it is non-toxic, fire-retardant and permanently fills and seals cracks and gaps.

### Basic Use

Apply Touch 'n Seal No-Warp foam one-component expanding polyurethane foam sealant using a foam applicator gun to seal cracks and gaps up to 1-1/2" (38mm) wide. No-Warp foam provides a non-warping, permanent insulating and air sealing solution to building component materials including wood, masonry, insulating foam boards, metal, plastics and sheetrock.

Use Touch 'n Seal Poly-Clean foam cleaner to clean wet No-Warp foam from hands, tools and foam applicator guns.

### Composition & Materials

Touch 'n Seal No-Warp polyurethane one-component expanding foam sealant is a permanent, bright white, hypoallergenic foam sealant that dries within minutes of

application. No-Warp is non-toxic and will not decompose with age.

### Sizes

Gun Foam – Item # 4004529712  
20 ounce (567 gm)

### Features/Benefits

- Will not bow or bind door, window or skylight frames and jambs
- Provides a permanent seal against air, moisture and insect infiltration
- Does not shrink as do many caulk type sealants
- Expands to fill gaps up to 1-1/2" (38mm) wide reducing air exchanges
- Bonds to common building materials including wood, concrete, insulating foam boards, metal, plastics and sheetrock
- Reduces energy loss
- Reduces use of fossil fuels and improves air quality
- No Ozone Depleting Chemicals
- Helps to reduce Green House Gas Emissions
- Allows for down sized HVAC systems; uses less energy, fewer cycle times, more consistent "comfort level", reduces equipment maintenance
- Fire-retardant
- Bright white color

### Limitations

- Foam is combustible. Do not expose to temperatures above 240°F(116°C), open flames or sparks.
- Do not expose to ultraviolet light.
- Chemicals must be 50°-100°F (10°38°C) prior to application.
- Do not store in temperatures above 120°F (49°C).
- Always refer to local building code regulations.
- 1 component foams are not suitable for covering large areas or voids such as sill plates, headers or in stud wall cavities. Refer to ICC-ESR 1926 for Fireblock applications. Refer to local building codes for details specific to your area.
- Propellant is flammable. Read MSDS and do not use near high heat, sparks or open flame.

## 4. TECHNICAL DATA

### Applicable Standards

- ASTM E-84 Surface Burning Characteristics



- ASTM E-283 Air Leakage
- ASTM C-518 R-Value
- ASTM C-1536 Yield
- ASTM D-1622 Core Density

### Approvals/Certifications/Listings

- ICC ES ESR-1926
- International Building Code
- International Residential Code
- BOCA National Building Code
- 1999 Standard Building Code
- California Bureau of Home Furnishings and Insulation
- Conforms to AAMA 812-04
- Underwriters Laboratories Classified Caulking & Sealants

### Physical/Chemical Properties

See Table.

### Shelf Life

12 months in unopened container when stored between 60°- 90°F (16°-32°C), in a dry, well ventilated area.

### Storage & Disposal

Keep containers tightly closed in a cool, well-ventilated area. Ideal storage temperature is 60°- 90°F (16°-32°C).

Storage above 90°F (32°C) will reduce shelf life. Do not store at temperatures above 120°F (49°C). Avoid freezing. Do not expose containers to conditions that may damage, puncture, or burst the containers. Dispose of leftover material/containers in accordance with Federal, state and local regulations. See Material Safety Data Sheet for more information.

## 5. INSTALLATION/APPLICATION

Always refer to local building codes prior to application of Touch 'n Seal® foam sealants.

Touch 'n Seal No-Warp foam one-component expanding foam sealant can



# TECH DATA SHEET

Thermal Protection 07 21 19  
Foamed In Place Insulation

be applied to and will adhere to almost any traditional construction surfaces including wood, masonry, insulating foam boards, metal, plastics and sheetrock.

Surfaces to receive Touch 'n Seal foam sealants must be dry, clean and free of dust, dirt, grease and other substances that may inhibit proper adhesion. For best results apply Touch 'n Seal one-component expanding foam sealants when surface and ambient temperatures are between 60°-90°F (16°-32°C). Chemical contents must be between 50°-100°F (10°-38°C) before dispensing. Use all chemical contents within 30 days of initial dispensing.

**Keep out of reach of children.** Always wear proper personal protective equipment, including gloves, clothing and eyewear. Use in well ventilated area. Please refer to manufacturer's instructions or request a faxed set of instructions from DAP by calling Customer Service at 800-325-6180.

Refer to manufacturer's Safe Use, Storage

and Handling For Low Pressure Spray Foam Products brochure prior to handling Touch 'n Seal materials. You may request a copy of this document from Customer Service at 800-325-6180 or by downloading from [www.touch-n-seal.com](http://www.touch-n-seal.com).

## 6. AVAILABILITY & COST

### Availability

Touch 'n Seal polyurethane foams are available throughout the U.S., Canada, Mexico and the world. Contact Convenience Products Customer Service at 800-325-6180 or FAX 636-349-5335 for distributor information.

### Cost

Contact Convenience Products for local distributors who can provide cost and delivery information.

## 7. WARRANTY

If product fails to perform when used as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP will not be responsible for incidental or consequential damages.

## 8. MAINTENANCE

None.

## 9. TECHNICAL SERVICES

Technical assistance, including more detailed information, product literature, test results, assistance with preparing project specifications and application training is available by contacting 1-888-DAP-TIPS.

## 10. FILING SYSTEMS

Additional information is available from the manufacturer upon request.

The information contained herein was accurate at the time of publishing. Please refer to the Touch 'n Seal website for the latest information.

### TYPICAL PROPERTIES OF TOUCH 'N SEAL NO-WARP POLYURETHANE FOAM SEALANT

Shelf Life	1 year; unopened container	
Surface Dry Time/Surface Tack Free Time	Approx. 10 min. @ 72°F/50% R.H.	
Fully Cured	Approx. 1 hour	
Cuttability	Approx. 30 minutes	
ASTM E-84 Surface Burning Characteristics	UL-723 (four - 1/2" beads)	ULC-S102 (four - 12.8mm beads)
Flame Spread	10	5
Smoke Development	15	10
ASTM E-283 Air Leakage	< 0.01cfm @ 50mph	
ASTM C-518-4 R-Value	4 - 5 /in. (25mm)	
ASTM C-1536 Yield	2,200 linear feet (670m) @ 1/4" (6.4 mm) dia. bead	
ASTM D-1622 Core Density	1.3 - 1.8 PCF	
International Building Code	Conforms	
International Residential Code	Conforms	
BOCA National Building	Conforms	
1999 Standard Building Code	Conforms	
ICC-ES	ESR-1926	
California Bureau of Home Furnishings and Insulation	Listed	
AAMA 812-04	Conforms	
NFPA 30B Classification	Aerosol Level 2	
Underwriters Laboratories Classified Caulking & Sealants	UL	ULC
	BLIS.R14175,	BLEZC.R14175