

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Touch 'n Seal Storm Bond
- **Article number:** EHS 9470 StormBond
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Sealant
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Convenience Products, division of Clayton Corp.
866 Horan Drive
Fenton, MO 63026-2416
Phone: 636-349-5855
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585



SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.



health hazard

- | | | |
|---------------|------|--|
| Resp. Sens. 1 | H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Carc. 2 | H351 | Suspected of causing cancer. |
| STOT RE 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |



- | | | |
|-------------------|------|--|
| Acute Tox. 4 | H332 | Harmful if inhaled. |
| Skin Irrit. 2 | H315 | Causes skin irritation. |
| Eye Irrit. 2 | H319 | Causes serious eye irritation. |
| Skin Sens. 1 | H317 | May cause an allergic skin reaction. |
| STOT SE 3 | H335 | May cause respiratory irritation. |
| ----- | | |
| | H229 | Pressurised container: May burst if heated. |
| Aquatic Chronic 3 | H412 | Harmful to aquatic life with long lasting effects. |

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

- | | |
|---------|---|
| R20-40: | Harmful by inhalation. Limited evidence of a carcinogenic effect. |
|---------|---|

(Contd. on page 2)

Safety Data Sheet


according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014


Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 1)

 Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

 Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomeres and homologues

tris[2-chloro-1-(chloromethyl)ethyl] phosphate

4,4'-methylenediphenyl diisocyanate

trans-dichloroethylene

· **Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

H229 Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 2)

- P251 Pressurized container: Do not pierce or burn, even after use.
 P260 Do not breathe mist/vapours/spray.
 P281 Use personal protective equipment as required.
 P264 Wash thoroughly after handling.
 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Contains isocyanates. May produce an allergic reaction.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

3,2 % by mass of the contents are flammable

· **Hazard description:**

· **WHMIS-symbols:**

D2A - Very toxic material causing other toxic effects



· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 0

Reactivity = 1

· **HMIS-ratings (scale 0 - 4)**



Health = *1

Fire = 0

Reactivity = 1

* - Indicates a long term health hazard from repeated or prolonged exposures.

· **HMIS Long Term Health Hazard Substances**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues
101-68-8	4,4'-methylenediphenyl diisocyanate

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS
















Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 3)

Dangerous components:

CAS: 9016-87-9	diphenylmethanediisocyanate, isomers and homologues  Carc. Cat. 3  	10-25%
CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9	4,4'-methylenediphenyl diisocyanate  Carc. Cat. 3  	10-25%
CAS: 811-97-2 EINECS: 212-377-0	Norflurane R44 	15-25%
CAS: 13674-87-8 EINECS: 237-159-2 Index number: 015-199-00-X	tris[2-chloro-1-(chloromethyl)ethyl] phosphate   	2,5-10%
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate R52/53 Aquatic Chronic 3, H412	2,5-10%
CAS: 156-60-5 EINECS: 205-860-2 Index number: 602-026-00-3	trans-dichloroethylene  R52/53   Aquatic Chronic 3, H412	2,5-10%
CAS: 68476-85-7 EINECS: 270-704-2 Index number: 649-202-00-6	Petroleum gases, liquefied   Press. Gas C, H280	≤ 2,5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 4)

In case of irregular breathing or respiratory arrest provide artificial respiration.

· **After skin contact:**

Do not pull solidified product off the skin.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

In cases of frostbite, rinse with plenty of water. Do not remove clothing.

· **After eye contact:**

Immediately remove contact lenses if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

Asthma attacks

Breathing difficulty

Dizziness

Coughing

Allergic reactions

Irritant to skin and mucous membranes.

Irritant to eyes.

May cause respiratory irritation.

Gastric or intestinal disorders when ingested.

· **Hazards**

Danger of impaired breathing.

Danger of pulmonary oedema.

Danger of pneumonia.

Possible risk of irreversible effects.

Harmful if inhaled.

Danger of serious damage to health by prolonged exposure.

Limited evidence of a carcinogenic effect.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

Contains diphenylmethanediisocyanate, isomeres and homologues, 4,4'-methylenediphenyl diisocyanate.

May produce an allergic reaction.

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

Medical supervision for at least 48 hours.

Monitor circulation, possible shock treatment.

If necessary oxygen respiration treatment.

Contains isocyanates. May produce an allergic reaction.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

· **For safety reasons unsuitable extinguishing agents:** None.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 5)

- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
Danger of receptacles bursting because of high vapour pressure when heated.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Isolate area and prevent access.
- **6.2 Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Allow to solidify. Pick up mechanically.
Absorb liquid components with liquid-binding material.
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Use only in well ventilated areas.
Avoid splashes or spray in enclosed areas.
- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
Provide ventilation for receptacles.
Store in a cool location.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidising agents.
Do not store together with acids.
- **Further information about storage conditions:**
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 6)

Protect from heat and direct sunlight.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.· **8.1 Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****101-68-8 4,4'-methylenediphenyl diisocyanate**

PEL (USA)	Ceiling limit: 0,2 mg/m ³ , 0,02 ppm
REL (USA)	Long-term value: 0,05 mg/m ³ , 0,005 ppm Ceiling limit: 0,2* mg/m ³ , 0,02* ppm *10-min
TLV (USA)	Long-term value: 0,051 mg/m ³ , 0,005 ppm
EL (Canada)	Long-term value: 0,005 ppm Ceiling limit: 0,01 ppm Skin; S
EV (Canada)	Long-term value: 0,005 ppm Ceiling limit: 0,02 ppm

811-97-2 Norflurane

WEEL (USA)	Long-term value: 1000 ppm
------------	---------------------------

156-60-5 trans-dichloroethylene

PEL (USA)	Long-term value: 790 mg/m ³ , 200 ppm
REL (USA)	Long-term value: 790 mg/m ³ , 200 ppm
TLV (USA)	Long-term value: 793 mg/m ³ , 200 ppm
EL (Canada)	Long-term value: 200 ppm
EV (Canada)	Short-term value: 990 mg/m ³ , 250 ppm Long-term value: 790 mg/m ³ , 200 ppm

68476-85-7 Petroleum gases, liquefied

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F: minimal oxygen content
EL (Canada)	Short-term value: 1250 ppm Long-term value: 1000 ppm
EV (Canada)	Long-term value: 1,000 ppm

· **DNELs** No further relevant information available.· **PNECs** No further relevant information available.· **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 7)

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Respiratory protection:**



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Contact lenses should not be worn.



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 8)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

 Form: Aerosolized liquid with compressed gas in cylinders

 Colour: Grey

· Odour: Petroleum-like

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

 Melting point/Melting range: Not Determined.

 Boiling point/Boiling range: -15 ° F / -26 °C

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gaseous): Not applicable.

· Auto/Self-ignition temperature: 752 ° F / 400 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not self-igniting.

· Danger of explosion: Not determined.

· Explosion limits:

 Lower: Not determined.

 Upper: Not determined.

· Vapour pressure at 20 °C: 5716 hPa

· Density at 20 °C: 1,2 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

 water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

 Dynamic: Not determined.

 Kinematic: Not determined.

· Solvent content:

 VOC content: 21,0 %

 VOC (US EPA Method 24) 37 g/l

· 9.2 Other information: No further relevant information available.

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 9)

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions**
Toxic fumes may be released if heated above the decomposition point.
Reacts with strong oxidising agents.
Reacts with alcohols, amines, aqueous acids and alkalis.
- **10.4 Conditions to avoid** Store away from oxidising agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Nitrogen oxides
Isocyanate
Chlorine compounds
Fluorocarbons
Phosphorus compounds

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral	LD50	2200 mg/kg (mouse)
------	------	--------------------

13674-87-8 tris[2-chloro-1-(chloromethyl)ethyl] phosphate

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitisation:**
Sensitisation possible through inhalation.
Sensitisation possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant
Danger through skin adsorption.
Toxic and/or corrosive effects may be delayed up to 24 hours.
Suspected of causing cancer.
- **Sensitisation:** May cause sensitisation by inhalation and skin contact.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 10)

- **Repeated dose toxicity:**
May cause damage to organs through prolonged or repeated exposure.
Repeated exposures may result in skin and/or respiratory sensitivity.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):**
Carc. 2

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

13674-87-8 tris[2-chloro-1-(chloromethyl)ethyl] phosphate

LC50	1,1 mg/l (Oncorhynchus mykiss) 96 h
------	--

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 11)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **DOT** Aerosols
- **ADR** 1950 AEROSOLS
- **IMDG, IATA** AEROSOLS
- **14.3 Transport hazard class(es)**

- **DOT**



- **Class** 2.2
- **Label** 2.2

- **ADR, IMDG, IATA**



- **Class** 2.2
- **Label** 2.2
- **14.4 Packing group**
- **DOT, ADR, IMDG, IATA** Not Regulated
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Not applicable.
- **EMS Number:** F-D,S-U
- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

- **Transport/Additional information:**

- **ADR**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

- **IMDG**
- **Limited quantities (LQ)** 0
- **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

· UN "Model Regulation":

UN1950, AEROSOLS, 2.2

(Contd. of page 12)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

· Chemicals known to cause cancer:

13674-87-8 tris[2-chloro-1-(chloromethyl)ethyl] phosphate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic Categories

· EPA (Environmental Protection Agency)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

CBD

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

156-60-5 trans-dichloroethylene

II

· IARC (International Agency for Research on Cancer)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

3

101-68-8 4,4'-methylenediphenyl diisocyanate

3

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Canada

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

(Contd. on page 14)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 13)

· **Canadian Ingredient Disclosure list (limit 0.1%)**

101-68-8	4,4'-methylenediphenyl diisocyanate
----------	-------------------------------------

· **Canadian Ingredient Disclosure list (limit 1%)**

None of the ingredients are listed.

· **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
.....	
R11	Highly flammable.
R12	Extremely flammable.
R20	Harmful by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R40	Limited evidence of a carcinogenic effect.
R42/43	May cause sensitisation by inhalation and skin contact.
R44	Risk of explosion if heated under confinement.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation

(Contd. on page 15)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 25.11.2014

Revision: 25.11.2014

Trade name: Touch 'n Seal Storm Bond

(Contd. of page 14)

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Gas 1: Flammable gases, Hazard Category 1
: Flammable aerosols, Hazard Category 3
Press. Gas C: Gases under pressure: Compressed gas
Flam. Liq. 1: Flammable liquids, Hazard Category 1
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 2: Carcinogenicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Sources

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com

4004517184