

# MATERIALS CREDITS DOCUMENTATION SHEET

## LEED™ - GREEN BUILDING RATING SYSTEM

<b>MATERIALS OR PRODUCT:</b>		<b>TOUCH 'N SEAL 1.0 PCF FR Low Density Open Cell Foam</b>	
<b>MATERIAL COST (LESS LABOR AND EQUIPMENT):</b>			
<b>Contractor/Installer:</b>	<b>Manufacturer:</b>	Convenience Products	
<b>Address:</b>	<b>Manufacturer Address:</b>	866 Horan Drive Fenton MO 63026	
<b>Manufacturer Contact: Michael Sites, Technical Services Manager, (800) 325-6180</b>			

Signed by: Michael Sites Date 4/11/16  
 Company: Convenience Products

*Instructions to Contractor/Installer: Please complete the following information in all appropriate categories. Use one documentation sheet for each product or material (e.g. tile and grout each get their own sheet). Attach any other additional information to this sheet (e.g. cut sheets, letters from manufacturers, etc.)*

### **LEED v4 for Building Design and Construction: Homes**

#### **Step A – Energy and Atmosphere**

- Performance Path – Annual Energy Use (1-29 points possible)
- Prescriptive Path – Air Infiltration (1-2 points possible)
- Prescriptive Path – Envelope Insulation (1-2 points possible)

<b>1.0 PCF Low Density</b>	Functions as an air barrier and thermal insulation, this polyurethane foam product helps building to achieve higher levels of energy efficiency.
----------------------------	--

#### **Step B – Materials & Resources**

- Construction Waste Management (0.5-3 points possible)

<b>1.0 PCF Low Density</b>	This foam sealant expands and seals without requiring trimming; results in no waste. Steel can is able to be recycled.
----------------------------	--

#### **Step C – Indoor Environmental Quality**

- Low-Emitting Products (1-3 points possible)

<b>1.0 PCF Low Density</b>	0 g/l; below CA SCAQMD Rule 1168 limits of 250 g/L VOC for Architectural Sealants.
----------------------------	--

LEED SUBMITTALS