

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

1 Identification

- **Product identifier**
- **Trade name:** Touch 'n Seal Panel Bond Polyurethane Foam Adhesive
- **Article number:** EHS 9456
- **Recommended use and restriction on use**
- **Recommended use:** Sealant
- **Restrictions on use:** Contact manufacturer
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Convenience Products, Foam Products Division
307 Integram Drive
Pacific, MO 63036
Phone: 636-349-5855
Toll-Free: 1-800-325-6180
- **Emergency telephone number:**
ChemTel Inc.
+1 (800)255-3924, +1 (813)248-0585



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Lact. H362 May cause harm to breast-fed children.

- **Additional information:**

There are no other hazards not otherwise classified that have been identified.

0 % of the mixture consists of component(s) of unknown toxicity.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 1)

· **Hazard pictograms:**



GHS04 GHS07 GHS08

· **Signal word:** Danger

· **Hazard-determining components of labeling:**

4,4'-methylenediphenyl diisocyanate
 halogenated hydrocarbon
 Alkanes, chloro
 diphenylmethanediisocyanate, isomers and homologues

· **Hazard statements:**

H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H362 May cause harm to breast-fed children.
 H335 May cause respiratory irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements:**

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P263 Avoid contact during pregnancy/while nursing.
 P260 Do not breathe mist/vapors/spray.
 P284 In case of inadequate ventilation wear respiratory protection.
 P264 Wash thoroughly after handling.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P314 Get medical advice/attention if you feel unwell.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P405 Store locked up.
 P410+P403 Protect from sunlight. Store in a well-ventilated place.
 P412 Do not expose to temperatures exceeding 50°C/122°F.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 2)

- **Classification system**
- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 0
Reactivity = 3

- **HMIS-ratings (scale 0 - 4)**



Health = *1
Fire = 0
Reactivity = 3

* - Indicates a long term health hazard from repeated or prolonged exposures.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

101-68-8	4,4'-methylenediphenyl diisocyanate ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	10-25%
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues ⚠ Resp. Sens. 1, H334; STOT RE 2, H373 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	10-25%
811-97-2	Norflurane ⚠ Press. Gas, H280 Simple Asphyxiant	10-25%
156-60-5	halogenated hydrocarbon ⚠ Flam. Liq. 2, H225 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	2.5-10%

- **Additional information:**

For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.
For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

- **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 3)

Provide oxygen treatment if affected person has difficulty breathing.
In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Do not pull solidified product away from the skin.
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

- **After eye contact:**

Immediately remove contact lenses if possible.
Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.
Do not induce vomiting; immediately call for medical help.

- **Information for doctor**

- **Most important symptoms and effects, both acute and delayed:**

Asthma attacks
Headache
Breathing difficulty
Allergic reactions
Coughing
Nausea
Gastric or intestinal disorders when ingested.
Irritant to skin and mucous membranes.
Irritant to eyes.
Dizziness
Disorientation

- **Danger:**

Danger of impaired breathing.
Danger of disturbed cardiac rhythm.
Danger of pulmonary edema.
Danger of pneumonia.
Danger of convulsion.

- **Indication of any immediate medical attention and special treatment needed:**

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.
Treat skin and mucous membrane with antihistamine and corticoid preparations.
In cases of irritation to the lungs, initial treatment with corticoid steroid inhalants.
Monitor circulation.
If necessary oxygen respiration treatment.
Medical supervision for at least 48 hours.
Contains isocyanates. May produce an allergic reaction.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

- **For safety reasons unsuitable extinguishing agents:** Water stream.

- **Special hazards arising from the substance or mixture**

Danger of receptacles bursting because of high vapor pressure if heated.
During heating or in case of fire poisonous gases are produced.

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 4)

- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information:** Cool endangered product with water spray.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures:**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation.
Protect from heat.
Isolate area and prevent access.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Allow to solidify. Pick up mechanically.
Send for recovery or disposal in suitable receptacles.
Dispose contaminated material as waste according to item 13.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
Keep away from heat and direct sunlight.
Use only in well ventilated areas.
- **Information about protection against explosions and fires:**
Keep respiratory protective device available.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
Provide ventilation for receptacles.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidizing agents.
- **Further information about storage conditions:**
Protect from heat and direct sunlight.
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

· **Specific end use(s):** No relevant information available.

(Cont'd. of page 5)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL (USA)	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
REL (USA)	Long-term value: 0.05 mg/m ³ , 0.005 ppm Ceiling limit value: 0.2* mg/m ³ , 0.02* ppm *10-min
TLV (USA)	Long-term value: 0.051 mg/m ³ , 0.005 ppm
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin; S
EV (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm
LMPE (Mexico)	Long-term value: 0.005 ppm

811-97-2 Norflurane

WEEL (USA)	Long-term value: 1000 ppm
------------	---------------------------

156-60-5 halogenated hydrocarbon

PEL (USA)	Long-term value: 790 mg/m ³ , 200 ppm
REL (USA)	Long-term value: 790 mg/m ³ , 200 ppm
TLV (USA)	Long-term value: 793 mg/m ³ , 200 ppm
EL (Canada)	Long-term value: 200 ppm
EV (Canada)	Short-term value: 990 mg/m ³ , 250 ppm Long-term value: 790 mg/m ³ , 200 ppm
LMPE (Mexico)	Long-term value: 200 ppm

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Clean skin thoroughly immediately after handling the product.

· **Engineering controls:** Use only outdoors or in a well-ventilated area.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 6)

· **Breathing equipment:**



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment** No relevant information available.

· **Risk management measures** See Section 7 for additional information.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General information**

· **Appearance:**

· Form:	Aerosol
· Color:	Amber colored
· Odor:	Light Petroleum-like

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition:**

· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** The product is not flammable.

· **Auto-ignition temperature:** Not determined.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not self-igniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· Lower:	Not determined.
-----------------	-----------------

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 7)

Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.00-1.10 g/cm ³ (8.345-9.18 lbs/gal)
· Relative density:	Not determined.
· Vapor density:	Not determined.
· Evaporation rate:	Not applicable.
· Solubility in / Miscibility with:	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
VOC content:	155 g/l (US EPA Method 24)
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions:**
Danger of receptacles bursting because of high vapor pressure if heated.
Contact with acids releases toxic gases.
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid:** Store away from oxidizing agents.
- **Incompatible materials:** No relevant information available.
- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Nitrogen oxides (NOx)
Hydrogen cyanide (prussic acid)
Phosphorus oxides (e.g. P2O5)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral | LD50 | 2200 mg/kg (mouse)

13674-84-5 tris(2-chlorisopropyl)-phosphate

Oral | LD50 | 3600 mg/kg (rat)

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 8)

156-60-5 halogenated hydrocarbon

Oral	LD50	770 mg/kg (rat)
------	------	-----------------

- **Primary irritant effect:**

- **On the skin:** Irritant to skin and mucous membranes.

- **On the eye:** Irritating effect.

- **Subacute to chronic toxicity:**

Inhalation of concentrated vapors as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

- **Additional toxicological information:**

In addition to local irritant manifestations, there is a narcotic effect when inhaling high concentrations, with high danger of central respiratory arrest.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

101-68-8	4,4'-methylenediphenyl diisocyanate	3
----------	-------------------------------------	---

9016-87-9	diphenylmethanediisocyanate, isomers and homologues	3
-----------	---	---

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

- **Probable route(s) of exposure:**

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- **Acute effects (acute toxicity, irritation and corrosivity):** Irritating to eyes, respiratory system and skin.

- **Repeated dose toxicity:**

May cause damage to organs through prolonged or repeated exposure.

Repeated exposures may result in skin and/or respiratory sensitivity.

Suspected of causing cancer.

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Carc. 2, Lact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

- **STOT-single exposure:** May cause respiratory irritation.

- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No relevant information available.

- **Persistence and degradability:** No relevant information available.

- **Behavior in environmental systems**

- **Bioaccumulative potential:** No relevant information available.

- **Mobility in soil:** No relevant information available.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 9)

- **Additional ecological information**

- **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- **Other adverse effects:** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- **Uncleaned packagings**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- **DOT, ADR, IMDG, IATA** UN1950

- **UN proper shipping name**



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 1 L (0.3 gal).

- **DOT**
- **ADR**
- **IMDG**
- **IATA**

Aerosols
1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
AEROSOLS, MARINE POLLUTANT
Aerosols, non-flammable

- **Transport hazard class(es)**

- **DOT**



- **Class**

2.2

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 10)

· **Label** 2.2

· **ADR**

· **Class** 2 5A Gases

· **Label** 2.2

· **IMDG**

· **Class** 2.2

· **Label** 2.2

· **IATA**

· **Class** 2.2

· **Label** 2.2

· **Packing group** Aerosols are not assigned a packing group.

· **Environmental hazards**

· **Marine pollutant:** Symbol (fish and tree)

· **Special marking (ADR):** Symbol (fish and tree)

· **Special precautions for user** Warning: Gases

· **Danger code (Kemler):** -

· **EMS Number:** F-D,S-U

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

· **UN "Model Regulation"** UN 1950 AEROSOLS, 2.2

(Cont'd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 11)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 304 (emergency release notification):**

None of the ingredients are listed.

· **Sections 311/312 (hazardous chemical threshold planning quantity in pounds):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

101-68-8 | 4,4'-methylenediphenyl diisocyanate

9016-87-9 | diphenylmethanediisocyanate, isomeres and homologues

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency):**

101-68-8 | 4,4'-methylenediphenyl diisocyanate

D, CBD

9016-87-9 | diphenylmethanediisocyanate, isomeres and homologues

CBD

156-60-5 | halogenated hydrocarbon

II

· **IARC (International Agency for Research on Cancer):**

101-68-8 | 4,4'-methylenediphenyl diisocyanate

3

9016-87-9 | diphenylmethanediisocyanate, isomeres and homologues

3

· **TLV (Threshold Limit Value established by ACGIH):**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

(Cont'd. on page 13)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 10/30/2015

Reviewed on 10/30/2015

Trade name: Touch 'n Seal Panel Bond Polyurethane Foam Adhesive

(Cont'd. of page 12)

- **Canadian substance listings**

- **Canadian Domestic Substances List (DSL):**

All ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 0.1%):**

101-68-8	4,4'-methylenediphenyl diisocyanate
----------	-------------------------------------

- **Canadian Ingredient Disclosure list (limit 1%):**

None of the ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of preparation / last revision** 10/30/2015 / -

- **Abbreviations and acronyms:**

Press. Gas: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Lact.: Reproductive toxicity, Additional category, Effects on or via lactation

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

- **Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com